

Option Switch

- ► M Mix Mode
 - ON Mixed Mode
 - OFF L&R connected Tank/Separate Mode
 - OFF L or R connected Mirror Mode
- ► B Brake Mode
 - ON Brake
 - OFF Coast
- ▶E Expo Mode
 - ON Expo response
 - OFF Linear response
- ► L Lipo Cutoff
 - ON Lipo cutoff active
 - OFF Lipo cutoff ignored

Calibration Procedure

- 1. Center controls and trims
- 2. Press and hold Cal button until Status LED goes out (about 3 seconds), release button Status LED blinks fast
- 3. Move sticks to full extent several times
- 4. Center sticks
- 5. Press and release Cal button to store settings and resume normal operation

<u>Special:</u> Enter & Exit Calibration mode with no signal or without moving sticks to restore factory settings

Option Switch

- ► M Mix Mode
 - ON Mixed Mode
 - OFF L&R connected Tank/Separate Mode
 - OFF L or R connected Mirror Mode
- ► B Brake Mode
 - ON Brake
 - OFF Coast
- ►E Expo Mode
 - ON Expo response
 - OFF Linear response
- ► L Lipo Cutoff
 - ON Lipo cutoff active
 - OFF Lipo cutoff ignored

Calibration Procedure

- 1. Center controls and trims
- 2. Press and hold Cal button until Status LED goes out (about 3 seconds), release button Status LED blinks fast
- 3. Move sticks to full extent several times
- 4. Center sticks
- 5. Press and release Cal button to store settings and resume normal operation

<u>Special:</u> Enter & Exit Calibration mode with no signal or without moving sticks to restore factory settings